Revision: 18.11.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.11.2022

Version number 104.01 (replaces version 104.00)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name LP407/13
- **UFI**: 0204-J067-D006-PAC0
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Cleaning material/ Detergent

Restrictions on use apply to this product according to Regulation (EU) no. 1907/2006 Annex XVII (see section 15)

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Riepe GmbH & Co. KG

Theodor Rosenbaum Str. 28-30

32257 Bünde - Deutschland

Tel.: +49 (0) 5223 - 687407-0

Fax: +49 (0) 5223 - 687407-50

E-Mail: info@riepe.eu

- Informing department:

Tel.: +49 (0) 5223 - 687407-0

E-mail: info@riepe.eu

- 1.4 Emergency telephone number:

Poison Control Center, Mainz

Tel. 00 49 / 61 31 / 19 240

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling: acetone
- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 1)

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.- vPvB: Not applicable.
- Determination of endocrine-disrupting properties
 78-93-3 2-Butanone List II

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of the substances listed below with harmless additions

- Dangerous components:			
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	50-100%	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%	
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥2.5-<10%	
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	2-Butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤1%	

- Additional information For the wording of the listed hazard phrases refer to section 16.
- Composition/Ingredients

Constituents according to EC-Regulation 648/2004:

Perfumes (d-Limonene),

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General advice: Instantly remove any clothing soiled by the product.
- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact

Instantly wash with water and soap and rinse thoroughly. If skin irritation persists, seek medical advice.

- After eye contact

Rinse immediately opened eye for several minutes under running water. Then consult doctor.

- After swallowing

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)

Printing date 18.11.2022

Version number 104.01 (replaces version 104.00)

Trade name LP407/13

(Contd. of page 2)

Revision: 18.11.2022

Do not induce vomiting; instantly call for medical help.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures. In case of incomplete combustion carbon monoxide can arise. Fumes are heavier than air and distributed over ground. Inflammation is possible from a far distance.

- 5.3 Advice for firefighters
- Protective equipment:

See section 8.

Wear full protective suit with self-contained breathing apparatus.

- Additional information

Endangered containers in the surrounding area should be cooled with a water-hose.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment and keep unprotected persons away.

Extinguish naked flames. Remove flammable sources. No smoking. Avoid sparks. Avoid contact with skin, eyes and clothing. Avoid inhalation of fumes. Air contaminated rooms thoroughly. Protect against electrostatic sparks.

- 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

Inform respective authorities in case product reaches water or sewage system.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Danger of explosion

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.

Ensure good ventilation/exhaustion at the workplace. Avoid repeated or long-term skin contact. Prevent formation of aerosols.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 3)

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage

Protect against direct sunlight, other sources of heat and ignition.

Store in cool, dry conditions in well sealed containers.

- Requirements to be met by storerooms and containers:

Observe official regulations on storage and handling of water harzardous substances

- Information about storage in one common storage facility:

Pay attention to regulations / technical guidelines on mixed storage of flammable liquids.

- Further information about storage conditions:

Pay attention to regulations/technical rules for the storage of combustible liquids.

Store in cool, dry conditions in well sealed containers.

- Storage class 3 (VCI Konzept, 2007)
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

 Compone 	ents with critical va	llues that require monitoring at the workplace:	
67-64-1 a	cetone		
IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm			
78-93-3 2-	Butanone		
IOELV (EU) Short-term value: 900 mg/m³, 300 ppm			
	Long-term value.	: 600 mg/m³, 200 ppm	
- DNELs			
64-17-5 et	hanol		
Oral	DNEL (population)	87 mg/kg bw/day (Long-term, systemic effects)	
Dermal	DNEL (worker)	8,238 mg/kg bw/day (Long-term, systemic effects)	
Inhalative	DNEL (worker)	380 mg/m³ (Long-term, systemic effects)	
	DNEL (population)	114 mg/m³ (Long-term, systemic effects)	
67-64-1 ad	cetone		
Oral	DNEL (population)	62 mg/kg bw/day (Long-term, systemic effects)	
Dermal	DNEL (worker)	186 mg/kg bw/day (Long-term, systemic effects)	
	DNEL (population)	62 mg/kg bw/day (Long-term, systemic effects)	
Inhalative	DNEL (worker)	2,420 mg/m³ (Acute, local effects)	
		1,210 mg/m³ (Long-term, systemic effects)	
	DNEL (population)	200 mg/m³ (Long-term, systemic effects)	
67-63-0 p	ropan-2-ol		
Oral	DNEL (population)	26 mg/kg bw/day (Long-term, systemic effects)	
Dermal	DNEL (worker)	888 mg/kg bw/day (Long-term, systemic effects)	
	DNEL (population)	319 mg/kg bw/day (Long-term, systemic effects)	
Inhalative	DNEL (worker)	500 mg/m³ (Long-term, systemic effects)	
	DNEL (population)	89 mg/m³ (Long-term, systemic effects)	
78-93-3 2-	Butanone		
Oral	DNEL (population)	31 mg/kg bw/day (Long-term, systemic effects)	
Dermal	DNEL (worker)	1,161 mg/kg bw/day (Long-term, systemic effects)	
			(Contd. on page

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

	חאבו	(nonulation)	442 mg/kg hu/day // ang tarm ayatamia affacta)	(Contd. of page 4)	
م بنام المام المام		(population)			
Inhalative			600 mg/m³ (Long-term, systemic effects)		
	DNEL	(population)	106 mg/m³ (Long-term, systemic effects)		
- PNECs					
64-17-5 et					
PNEC wat	ter	• •	ermittent releases)		
		0.96 mg/l (fre	,		
		0.79 mg/l (m	arine water)		
PNEC sec	liment	3.6 mg/kg dv	v (freshwater)		
		2.9 mg/kg dv	v (marine water)		
PNEC soil	1	0.63 mg/kg d	lw (soil)		
PNEC ST	Р	580 mg/l (se	wage plant)		
67-64-1 ad	cetone)			
PNEC wat	ter	10.6 mg/l (fre	eshwater)		
		1.06 mg/l (m	arine water)		
PNEC		21 mg/l (inter	21 mg/l (intermittent releases)		
100 mg/l (sewage plant)		wage plant)			
PNEC sediment 30.4 mg/kg dw (freshwater)					
3.04 mg/kg dw (marine water)					
PNEC soil					
67-63-0 pi	ropan-	2-ol			
		140.9 mg/l (freshwater)			
		140.9 mg/l (r	narine water)		
PNEC 2,251 mg/l (sewage plant)					
PNEC sediment 552 mg/kg dw (freshwater)					
		552 mg/kg d	w (marine water)		
PNEC 140.9 (intermittent releases)					
PNEC soil	1	28 mg/kg (soil)			
78-93-3 2-Butanone					
PNEC water 55.8 mg/l (freshwater)					
55.8 mg/l (marine water)					
PNEC sediment 284.74 mg/kg dw (freshwater)					
		284.7 mg/kg	dw (marine water)		
PNEC soil 22.5 mg/kg dw (soil)					
PNEC STP 709 mg/l (sewage plant)					

- Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls

Room ventilation i.e. vacuum suction. Measures to be taken against electro-static sparks.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Keep away from food, beverages and fodder.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 5)

Gases, fumes and aerosols should not be inhaled.

- Breathing equipment: Use breathing protection in case of insufficient ventilation.
- Recommended filter device for short term use:

Combination filter A-P2

(EN 14387)

- Hand protection Protective gloves.
- Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

Material of gloves is recommended for a short-term single use to protect from splashes. For permanent usage contact manufacturer of gloves.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection

Tightly sealed safety glasses.

(EN 166)

- Body protection:

Standard proctective clothing. Chemical resistant safety-shoes or boots. If skin contact is possible, wear inpenetrable protective clothing against this solvent. (EN 368)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information

- Colour: Yellow - Smell: Charact

- Smell: Characteristic
- Odour threshold: Not determined.

- Melting point/freezing point: 80 °C

- Boiling point or initial boiling point and boiling

range >65 °C

- Lower and upper explosion limit

- **Lower:** 2.5 Vol % (determined (EN 1839))

- Upper: 15 Vol % (ethanol)

- Flash point: <21 °C

Ignition temperature:
 Decomposition temperature:
 pH
 A25 °C (ethanol)
 Not determined.
 Not applicable.

Not determined.

- pH-value:

- Viscosity:

- Kinematic viscosity- dynamic:Not determined.Not determined.

- Solubility

- Water: Soluble

- Partition coefficient n-octanol/water (log value) Not determined.

- Vapour pressure at 50 °C: < 110 kPa (single components)

- Density and/or relative density

- Density at 20 °C 0.79 g/cm³

(Contd. on page 7)

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 6)

	, , , ,
- Relative density	Not determined.
- Vapour density	Not determined.
- 9.2 Other information	
- Appearance:	
- Form:	Fluid
- Important information on protection of hea	lth
and environment, and on safety.	
- Evaporation rate	Not determined.
-Information with regard to physical haza	nrd
classes	
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	
Highly flammable liquid and vapour.	
- Flammable solids	Void
 Self-reactive substances and mixtures 	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
 Self-heating substances and mixtures 	Void
- Substances and mixtures, which emit flamma	
gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

To avoid: warmth, flames, sparks

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

Formation of carbon monoxide and carbon dioxide in case of fire.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 7)

		(Conta. or pag
LD/LC50	values that	are relevant for classification:
64-17-5 et	thanol	
Oral	LD50	10,470 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC 50 / 4 h	>50 mg/l (rat) (OECD 403)
		>20 mg/l (mouse)
67-64-1 ad	cetone	
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	7,426-15,800 mg/kg (rbt)
Inhalative	LC 50 / 4 h	76 mg/l (rat)
67-63-0 pi	ropan-2-ol	
Oral	LD50	5,840 mg/kg (rat) (OECD 401)
		4,570 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
		13,400 mg/kg (rab)
Inhalative	LC 50 / 4 h	30 mg/l (rat)
78-93-3 2-	Butanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rbt)
Inhalative	LC 50 / 4 h	34.5 mg/l (rat)
		40 mg/l (mus)
		·

- Skin corrosion/irritation Less irritating. Remove lipid skin-film.
- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

- STOT-repeated exposure:			
64-17-5 ethanol			
Oral	Oral NOAEL 1,760 mg/kg (rat) (OECD 408, 90 d, target organ: liver)		
67-64	67-64-1 acetone		
Oral	NOAEL	900 mg/kg (rat) (KG/day 90 days)	
67-63-0 propan-2-ol			
Oral	NOAEL	900 mg/kg (rat) ((90d) OECD 408)	

- 11.2 Information on other hazards

- Endocrine disrupting properties	
78-93-3 2-Butanone	List II

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 8)

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:				
64-17-5 ethanol				
LC 50 / 48 h 8,140 mg/l (Leuciscus idus)				
EC 50 / 48 h >10,000 mg/l (Daphnia magna)				
EC 50 / 72 h 275 mg/l (Chlorella vulgaris) (OECD 201)				
67-64-1 acetone				
LC 50 / 96 h 7,500 mg/l (Leuciscus idus)				
5,540 mg/l (Oncorhynchus mykiss)				
EC 50 / 48 h 8,800 mg/l (Daphnia magna)				
EC 50 / 96 h 8,300 mg/l (Lepomis macrochirus)				
7,500 mg/l (Selenastrum capricornutum)				
67-63-0 propan-2-ol				
LC 50 / 96 h >10,000 mg/l (Pimephales promelas) (OECD 203 (Acute toxicity - fish))				
LC 50 / 48 h >100 mg/l (Leuciscus idus)				
EC 50 / 48 h >100 mg/l (Daphnia magna)				
EC 50 / 16 h 1,050 mg/l (Pseudomonas putida) (DIN 38412 T.8)				
EC 50 / 72 h >100 mg/l (Scenedesmus subspicatus)				
78-93-3 2-Butanone				
LC 50 / 96 h >3,000 mg/l (fish)				
EC 50 / 48 h 1,382 mg/l (Daphnia)				
- 12.2 Persistence and degradability				
67-63-0 propan-2-ol				

67-63-0 propan-2-ol

Biodegradability 49 % /BOD/ThBOD

Biodegradability 53 % /5 d, BSB5/CS (92/69/EG (L383) C.5 * Abbaubarkeit)

CSB 2.23 mg O2/g (Methode : Verordnung (EC) Nr. 440/2008, Anhang, C.)
BSB5 1.72 mg O2/g (Methode : Verordnung (EC) Nr. 440/2008, Anhang, C.)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects

- Respiratory inhibition of communal activated sludge EC 20 (mg/l according to ISO 8192 B):

64-17-5 ethanol

EC 50 (static) >100 mg/l (Chlorella pyrenoidosa) (OECD 201)

- Additional ecological information:
- General notes:

Do not allow to enter drainage system, surface or ground water Water hazard class 1 (Self-assessment): slightly hazardous for water.

EUE -

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 9)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

The following advice is related to new material and not to any processed products. In case of a mixture with other products other disposal methods may become necessary. If in doubt seek advice from product supplier or from local authorities.

- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. If possible, send to be recycled, otherwise burn or deposit in a certified facility.

- Waste disposal key number:

Since 01/01/99 the waste code numbers have not only been product-related but are also essentially application-related. The valid waste code number of the application can be obtained from the European waste catalogue.

- Uncleaned packagings: Disposal must be made according to official regulations.
- Recommendation:

Rented packaging: After optimal emptying, close immediately and return to the supplier without cleaning. Care should be taken that no other materials get into the packaging.

Other containers: After complete emptying and cleaning, send to be reconditioned or recycled.

Caution: Leftovers in the containers may cause the risk of explosion.

Uncleaned containers should not be perforated, cut or welded.

- Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport informatio	n
- 14.1 UN number or ID number - ADR/RID, IMDG, IATA	UN1993
- 14.2 UN proper shipping name - ADR/RID	1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHANOL (ETHYL ALCOHOL)), special provision 640D
- IMDG - IATA	FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHANOL (ETHYL ALCOHOL)) FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHANOL)
- 14.3 Transport hazard class(es) - ADR/RID - Class - Label	3 (F1) Flammable liquids. 3
- IMDG, IATA - Class - Label	3 Flammable liquids. 3
- 14.4 Packing group - ADR/RID, IMDG, IATA	II
- 14.5 Environmental hazards: - Marine pollutant:	Not applicable. No
14.6 Special precautions for userKemler Number:EMS Number:	<i>Warning: Flammable liquids.</i> 33 F-E, <u>S-E</u>

(Contd. on page 11)

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 10)

	(Contd. or page 10)
- Stowage Category	В
- 14.7 Maritime transport in bulk according to IM instruments	O Not applicable.
- Transport/Additional information:	
- ADR/RID - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Código E4 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHANOL (ETHYL ALCOHOL)), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:

acetone

- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 12)

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 11)

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Annex II REPORTABLE EXPLOSIVES PRECURSORS

 67-64-1 | acetone

 Regulation (EC) No 273/2004 on drug precursors

 67-64-1 | acetone | 3

 78-93-3 | 2-Butanone | 3

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

 67-64-1 | acetone | 3

 78-93-3 | 2-Butanone | 3
 - National regulations
 - Information about limitation of use:

Employment restrictions concerning young persons must be observed.

- Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

- **VOC (EU)** 789.7 q/l
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- UFI market placements:
- Relevant phrases

Complete wording of hazard statements and risk phrases (H- and R-phrases) mentioned in section 3. These phrases refer to the constituents. The labelling for this product is stated in section 2.

- Department issuing data specification sheet: see item 1: Informing department
- Date of previous version: 18.11.2022
- Version number of previous version: 104.00
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

LEV. Local Exhaust Ventilation

NOAEL: No Observed Adverse Effect Level

RPE: Respiratory Protective Equipment

RCR: Risk Characterisation Ratio (RCR= PEC/PNEC)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Classification, Labelling and Packaging (Regulation (EC) No. 1272/2008)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

Printing date 18.11.2022 Version number 104.01 (replaces version 104.00) Revision: 18.11.2022

Trade name LP407/13

(Contd. of page 12)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany) ISO: International Organisation for Standardisation

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- * Data compared to the previous version altered.

EUE -